

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)


PCT

(10) International Publication Number
WO 2005/038130 A1

- (15) International Patent Classification⁷: **D21F 3/02**
- (21) International Application Number:
PCT/SE2004/001486
- (22) International Filing Date: 15 October 2004 (15.10.2004)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data:
0302767-9 21 October 2003 (21.10.2003) SE
60/517,830 6 November 2003 (06.11.2003) US
- (71) Applicant (for all designated States except US): **METSO PAPER KARLSTAD AB** [SE/SE]; Box 1014, S-651 15 Karlstad (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **GUSTAVSSON, Tord, Gustav** [SE/SE]; Enåsgatan 5, S-667 33 Forshaga (SE).
- (74) Agent: **L-O LUNDQUIST PATENTBYRÅ AB**; Box 80, S-651 03 Karlstad (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: SUPPORT BODY, HOLDING DEVICE THEREFOR, APPARATUS WITH SUCH BODY FOR TREATMENT OF A WEB, METHODS OF FORMING AN EXTENDED NIP IN THE APPARATUS AND CONTROLLING LOAD IN THE NIP



(57) Abstract: A support body (7) for an apparatus having an extended nip (N) that is defined by a contact surface (13) of the support body and an opposed surface (4), the support body having two side surfaces (69, 70) facing from each other and connecting to the contact surface, and a bottom surface (71) facing from the contact surface, the support body being arranged to be moved towards the opposite surface by means of a loading system in order to load the nip via the contact surface. According to the invention the support body is elastically deformable and has its contact surface adaptable to the opposite surface in interaction therewith. The invention also relates to a holding device for such a support body and an apparatus, e.g. a press, for the treatment of a fibre web, said apparatus having such a support body. Furthermore, the invention relates to a method of forming the extended nip in said apparatus by loading the support body by means of the loading system, as well as a method of controlling the load in the extended nip by designing the support body with at least two layers with different elasticity providing a corresponding load profile.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*